


CRYSTAL Units

XTL90



Applications

- Bluetooth / Wireless LAN
- Wearable Devices
- LTE / SAS

Features

- Ultra thin / Dimensions (1.6×1.2×0.35)
- Ceramic Package
- High Reliability and High Stability



Specifications



Model	XTL90	
Nominal frequency range	24.000~80.000 MHz	
Crystal cut	Fundamental [AT-cut]	
Storage temperature range	-40 ~ +90 °C	
Operating temperature range	-30 ~ +85 °C	-30 ~ +105 °C
Frequency temperature characteristics(Ref. to +25°C)	$\pm 15 \times 10^{-6}$	$\pm 30 \times 10^{-6}$
Frequency tolerance (at +25°C)	$\pm 10 \times 10^{-6}$	
Equivalent series resistance	100Ω: 24.000~29.999 MHz	
	80Ω: 30.000~53.999 MHz	
	60Ω: 54.000~80.000MHz	
Load capacitance	8,10,12 pF or specify	
Shunt capacitance	3 pF max.	
Level of drive	10μW (100uW max.)	

Package quantity : 3,000pcs max./Reel

Outline and Dimensions [unit: mm]



Pin Connection	
#1,#3	Crystal
#2	GND
#4	GND(NC)

Land Pattern(REFERENCE)

